

LED replacement bulbs for flashlight

— E10 bulb base



RoHS



I. Basic Feature

1. It is much brighter than the original incandescent globe. As the most energy-saving lighting, it is lower power-consumption.
2. LED bulb is characterized by solid state lighting and eco-friendly product with no hazardous substances.
3. The lifespan of LED bulbs is over 50,000 hours.
4. It is convenient to replace the LED flashlight bulbs with various optional bulb colors to meet special occasions.
5. Adjustable to the standard E10 bulb holder. And it works better as a direct replacement of incandescent bulb on flashlight.
6. Deshun's LED bulbs are set inside high efficient LED constant drivers to ensure full electricity transmission.
7. Deshun's LED bulbs are set inside wide-ranging voltage LED constant drivers to adjust to different voltages flashlight, and assure the brightness steady. They are safe, stable, and reliable.

Deshun's bulbs are added into more practical functions:

1. The bulbs' heat is automatically varied with the bulb temperature. When the bulb's heat increases to some degree, the temperature control circuit will display its function and control the highest temperature within the safety scope. Of course, the intensity will be decreased at the same time.
2. Reverse Polarity Protection Circuit has been built in the LED bulbs, so even if the power supply is connected reversely the positive and negative of power supply, the LED bulb will not be damaged.



II. Outline

0.5W Flashlight LED bulb



1W / 3W Flashlight LED bulb



Chinese LED bulb



Luxeon LED bulb



Side emitting LED bulb

III. Size


Standard size

A: Overall dimension	22.50mm
B: Lens to top flange	8.30mm
C: The bottom to upper cap	20.30mm
D: Diameter of upper cap	9.80mm

Optional Size

We offer below size, and you can also specify your own ones.

A: Overall dimension	24.00mm
B: Lens to top flange	9.80mm
C: The bottom to upper cap	21.80mm
D: Diameter of upper cap	9.80mm






Model with parameter

Model	Bulb holder	Working Voltage (V)	LED Power(W)	Intensity (LM)	Light Angle	LED Type
D109L-0.5WCN35	E10	1.0~9.0	0.5	35	120	CN
DS109L-1WCN75	E10	1.0~9.0	1	75	120	CN
DS109L-1WCN100	E10	1.0~9.0	3	100	120	CN
DS630L-1WCN75	E10	6.0~30.0	1	75	120	CN
DS630L-1WCN100	E10	6.0~30.0	3	100	120	CN
DS0842L-3WCN150	E10	0.8~4.2	3	150	120	CN
DS3209L-3WCN150	E10	3.2~9.0	3	150	120	CN

Recommend Application Schematics:



Remarks:

If there are some difference with above specifications and parameters, please taking objects as standard

IV. Major Concerns

1. Operating temperature: -30°C~+60°C
2. Storage temperature: -40°C~+85°C
3. Humidity: 5%~90%
4. It features brighter on the high heat-emitting flashlight.

V. Typical Applications:

- Portable lighting
- Flashlights
- Head Lamps
- Lanterns
- Ceiling Light

VI. Package